

Package ‘SmarterPoland’

March 28, 2021

Type Package

Title Tools for Accessing Various Datasets Developed by the Foundation SmarterPoland.pl

Version 1.8

Author Przemyslaw Biecek (Foundation SmarterPoland.pl)

Maintainer Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

Description Tools for accessing and processing datasets prepared by the Foundation SmarterPoland.pl. Among all: access to API of Google Maps, Central Statistical Office of Poland, MojePanstwo, Eurostat, WHO and other sources.

LazyLoad yes

LazyData yes

LazyDataCompression xz

License GPL-3

Depends R (>= 3.0), ggplot2, httr, htmltools

Imports jsonlite, rjson

NeedsCompilation no

Repository CRAN

Date/Publication 2021-03-27 23:50:02 UTC

R topics documented:

SmarterPoland-package	2
Bank Danych Lokalnych	3
cities_lon_lat	4
countries	5
Dark Sky API for weather forecast	5
getEurostatDictionary	7
getEurostatRaw	8
getEurostatRCV	9
getEurostatTOC	10
getGoogleMapsAddress	11

getMillwardBrown	12
grepEurostatTOC	12
maturaExam	13

Index	14
--------------	-----------

SmarterPoland-package *Tools for Accessing Various Datasets Developed by the Foundation SmarterPoland.pl*

Description

Tools for accessing and processing datasets prepared by the Foundation SmarterPoland.pl. Among all: access to API of Google Maps, Central Statistical Office of Poland, Eurostat, WHO and other sources.

Details

Package: SmarterPoland
Type: Package
Version: 1.7
Date: 2016-03-21
License: GPL-3

Author(s)

Author: Przemyslaw Biecek (Foundation SmarterPoland.pl) Maintainer: Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

References

<http://www.smarterpoland.pl>

See Also

[getMillwardBrown](#), [getEurostatRCV](#), [getBDLseries](#), [getWeatherForecast](#)

Examples

```
## Not run:  
# download the dataset 'Pupil/Student - teacher ratio and average class' from eurostat  
# for more developed API see https://github.com/rOpenGov/eurostat  
tmp <- getEurostatRCV(kod = "educ_iste")  
head(tmp)
```

```
# download the dataset 'People killed in road accidents' from eurostat
# and plot a maptable for selected countries
# for more developed API see https://github.com/rOpenGov/eurostat
library(ggplot2)
t1 <- getEurostatRCV("tsdtr420")
t1 <- t1[t1$geo
ggplot(t1, aes(time, value, color=sex, group=sex)) +
  geom_line() + facet_wrap(~geo)

## End(Not run)
```

Bank Danych Lokalnych *API to Bank Danych Lokalnych [GUS]*

Description

Access to the GUS Bank Danych Lokalnych with the use of API developed by MojePanstwo.

Download and parse data from Bank Danych Lokalnych with the use of API developed by MojePanstwo.

Usage

```
getBDLtree(raw = FALSE, debug = 0)
getBDLsearch(query = "", debug = 0, raw = FALSE)
getBDLseries(metric_id = "", slice = NULL, time_range = NULL,
             wojewodztwo_id = NULL, powiat_id = NULL, gmina_id = NULL,
             meta = NULL, debug = 0, raw = FALSE)
getMPgminy(debug = 0)
getMPpowiaty(debug = 0)
getMPwojewodztwa(debug = 0)
```

Arguments

debug	Level of debug info. 0 for no debug, 1 or 2 for info about processed groups.
raw	If raw = TRUE the resulting JSON is returned without any transformation. For raw = FALSE results are transformed into a data.frame.
query	A query for DBL search.
metric_id	Metric id, if unknown then look for it in DBL tree or DBL search.
slice	A table with id dimensions, with format [1,34,*]. Use '*' to choose all dimensions (or use an empty string).
time_range	Year or range (like 2000:2010), empty means - full range.
wojewodztwo_id	Voievodship id or '*' for all.
powiat_id	County id of '*' for all. It's internal ID. Use getMPpowiaty() to get names and other information.
gmina_id	Subcounty id or '*' for all. It's internal ID. Use getMPgminy() to get TERYT codes.
meta	Should meta data be returned?

Value

The function `getMPgminy()` returns a data frame with identifiers `id/TERYT` for each subcounty.
The function `getMPpowiaty()` returns a data frame with identifiers `id` for each county.

The function `getBDLtree()` returns a data frame with identifiers of resources in Bank Danych Lokalnych.

Author(s)

Przemyslaw Biecek

References

The API of Bank Danych Lokalnych developed by `MojePanstwo` is described as https://mojepanstwo.pl/api/dane/get_

Examples

```
## Not run:  
# the data is downloaded and parsed from Internet  
# not that this dataset is pre-calculated in the package  
BDLtree <- getBDLtree(2)  
head(BDLtree)  
  
DBLtransport <- getBDLsearch("transport")  
head(DBLtransport)  
  
BDLseries <- getBDLseries(metric_id = 1)  
head(BDLseries)  
  
gminy <- getMPgminy()  
head(gminy)  
  
powiaty <- getMPpowiaty()  
head(powiaty)  
  
## End(Not run)
```

cities_lon_lat

Geocoordinates of Largest Cities

Description

A subset of `world.citiesmaps`. Extracted in order to shink number of dependencies. Only cities with `pop > 50k` are kept.

Author(s)

Przemyslaw Biecek [based on `world.cities`]

Examples

```
## Not run:
library(maps)
data(world.cities)
cities_lon_lat <- world.cities[!duplicated(world.cities$name),]
rownames(cities_lon_lat) = cities_lon_lat[,1]
cities_lon_lat <- cities_lon_lat[cities_lon_lat$pop > 50000,]
cities_lon_lat <- cities_lon_lat[,4:5]

## End(Not run)
```

countries

Birth and death rates, continent and population for selected countries

Description

Data from World Health Organization database <http://apps.who.int/gho/data/view.main.CBDR2040>.
Based on the example from Grammar of Graphics by Leland Wilkinson.

Author(s)

Przemyslaw Biecek [based on WHO data]

Examples

```
## Not run:
library(maps)
data(countries)
head(countries)

## End(Not run)
```

Dark Sky API for weather forecast

Access to Weather Forecasts with the Use of Dark Sky API.

Description

Access to hourly and daily weather forecasts with the use of Dark Sky API.

Usage

```
getWeatherForecast(apiKey, lat = NA, lon = NA, city = NA, raw=FALSE)
```

Arguments

apiKey	You need to have Dark Sky apiKey in order to access weather forecasts. See here: https://developer.forecast.io/ for more details.
lat	The latitude coordinate for which prediction has to be made.
lon	The longitude coordinate for which prediction has to be made.
city	Instead of lat and lon you may specify name of the city for which prediction has to be made.
raw	If TRUE then no parsing is done. The function <code>getWeatherForecast()</code> just download an forecast and returns it as a list.

Value

The function `getWeatherForecast()` returns list of three datasets. `now` and `by.hour` datasets contains predictions. For each timepoint following information are collected:

time, summary, icon, precipIntensity, precipProbability, temperature, apparentTemperature, dewPoint, humidity, windSpeed, windBearing, visibility, cloudCover, pressure, ozone, temperatureCelsius, apparentTemperatureCelsius

Daily predictions (`by.day` component) contain following information:

time, summary, icon, sunriseTime, sunsetTime, moonPhase, precipIntensity, precipIntensityMax, precipProbability, temperatureMin, temperatureMinTime, temperatureMax, temperatureMaxTime, apparentTemperatureMin, apparentTemperatureMinTime, apparentTemperatureMax, apparentTemperatureMaxTime, dewPoint, humidity, windSpeed, windBearing, visibility, cloudCover, pressure, ozone, precipIntensityMaxTime, precipType, temperatureMaxCelsius, temperatureMinCelsius, apparentTemperatureMaxCelsius, apparentTemperatureMinCelsius

Author(s)

Przemyslaw Biecek

References

The Dark Sky API for weather forecasts is described as <https://developer.forecast.io/>

Examples

```
## Not run:
# you have to have apiKey to execute these examples
library(scales)
library(ggplot2)

prognoza <- getWeatherForecast(apiKey, city='Warsaw')

ggplot(prognoza$by.hour, aes(y=temperatureCelsius, x=time)) +
  geom_line() + geom_point() +
  geom_point(data=prognoza$now, size=10, color='red') +
  theme(title=element_text(size=20),
        axis.text=element_text(size=20)) +
  scale_x_datetime(breaks = date_breaks("3 hour"),
```

```
        minor_breaks = date_breaks("1 hour"),
        labels = date_format("
ylab("") + xlab("") + ggtitle("Prognoza temperatury dla Warszawy")

## End(Not run)
```

getEurostatDictionary *Download a Dictionary from the Eurostat Database*

Description

Download a dictionary for given coded variable from Eurostat (ec.europa.eu/eurostat).

Usage

```
getEurostatDictionary(dictname)
```

Arguments

dictname Character, dictionary for given variable name will be downloaded.

Value

A data.frame with two columns, first with code names and second with full names.

Author(s)

Przemyslaw Biecek

References

The TOC is downloaded from the <http://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadList>.

See Also

See Also as [getEurostatRCV](#), [getEurostatRaw](#), [grepEurostatTOC](#).

Examples

```
## Not run:
tmp <- getEurostatDictionary("crop_pro")
head(tmp)

## End(Not run)
```

getEurostatRaw	<i>Download a Dataset from the Eurostat Database</i>
----------------	--

Description

Download a dataset from the eurostat database. The dataset is transformed into the tabular format.

Usage

```
getEurostatRaw(kod = "educ_iste", rowRegExp=NULL, colRegExp=NULL,  
strip.white = TRUE)
```

Arguments

kod	A code name for the data set of interested. See the table of contents of eurostat datasets for more details.
rowRegExp	If not NULL this regular expression will be used to filter rows out of downloaded file.
colRegExp	If not NULL this regular expression will be used to filter columns out of downloaded file.
strip.white	Passed to the internal <code>read.table()</code> . By default it strips white spaces from eurostat values.

Value

A dataset in data.frame format. First column contains names of cases. Column names usually corresponds to years.

Author(s)

Przemyslaw Biecek

References

Data is downloaded from <http://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadListing> website.

See Also

See Also as [getEurostatTOC](#), [getEurostatRaw](#), [grepEurostatTOC](#).

Examples

```
## Not run:  
tmp <- getEurostatRaw(kod = "educ_iste")  
head(tmp)  
  
## End(Not run)
```

getEurostatRCV *Download a Dataset from the Eurostat Database*

Description

Download a dataset from the eurostat database. The dataset is transformed into the molten / row-column-value format (RCV).

Usage

```
getEurostatRCV(kod = "educ_iste", ...)
```

Arguments

kod	A code name for the data set of interested. See the table of contents of eurostat datasets for more details.
...	Other parameters that are passed to <code>getEurostatRaw()</code> .

Value

A dataset in the molten format with the last column 'value'.

Author(s)

Przemyslaw Biecek

References

Data is downloaded from <http://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadListing> website.

See Also

See Also as [getEurostatTOC](#), [getEurostatRaw](#), [grepEurostatTOC](#).

Examples

```
## Not run:
tmp <- getEurostatRCV(kod = "educ_iste")
head(tmp)

t1 <- getEurostatRCV("rail_ac_catvict")
tmp <- cast(t1, geo ~ time, mean, subset=victim=="KIL" &
           pers_inv=="TOTAL" & accident=="TOTAL")
tmp3 <- tmp[,1:9]
rownames(tmp3) <- tmp3[,1]
tmp3 <- tmp3[c("UK", "SK", "FR", "PL", "ES", "PT", "LV"),]
matplot(2005:2012, t(tmp3[, -1]), type="o", pch=19, lty=1,
        las=1, xlab="", ylab="", yaxt="n")
```

```
axis(2,tmp3[,9], rownames(tmp3), las=1)

## End(Not run)
```

getEurostatTOC *Eurostat Table of Contents*

Description

Download a table of contents of eurostat datasets. Note that the values in column 'code' should be used to download a selected dataset.

Usage

```
getEurostatTOC()
```

Value

A data.frame with eight columns

title	The name of dataset of theme
code	The codename of dataset of theme, will be used by the getEurostatRCV and getEurostatRaw functions.
type	Is it a dataset, folder or table.
last.update.of.data, last.table.structure.change, data.start, data.end	Dates.

Author(s)

Przemyslaw Biecek

References

The TOC is downloaded from the <http://ec.europa.eu/eurostat/estat-navtree-portlet-prod/BulkDownloadList>.

See Also

See Also as [getEurostatRCV](#), [getEurostatRaw](#), [grepEurostatTOC](#).

Examples

```
## Not run:
tmp <- getEurostatTOC()
head(tmp)

## End(Not run)
```

getGoogleMapsAddress *Geolocalisation with Google Maps*

Description

Get geolocalisation (longitude, latitude) of a given address with the use of Google Maps API.

The Google Maps API is used to determine the geolocalisation (longitude, latitude) of a given address.

Usage

```
getGoogleMapsAddress(street = "Banacha 2", city = "Warszawa",  
country="Poland", positionOnly = TRUE, delay=1)
```

Arguments

street	An address (street and building number)
city	City
country	Country
positionOnly	What should be returned, vector with longitude, latitude coordinates or the raw result from Google Maps API
delay	Number of seconds to wait between api calls

Value

If positionOnly=TRUE then a vector with two values or a raw list from Google Maps otherwise.

Author(s)

Przemyslaw Biecek

References

The Google Maps API <https://developers.google.com/maps/>

Examples

```
## Not run:  
getGoogleMapsAddress()  
  
## End(Not run)
```

getMillwardBrown *MillwardBrown Pool Results*

Description

Download pool results from MillwardBrown website.

Usage

```
getMillwardBrown()
```

Value

A dataset in the molten format with pool date, party and percent of votes.

Author(s)

Maciej Beresewicz [data extraction] Przemyslaw Biecek [data melting]

Examples

```
## Not run:  
getMillwardBrown()  
  
## End(Not run)
```

grepEurostatTOC *Names of Eurostat Datasets That Fit Given Pattern*

Description

Lists names of dataset from eurostat with the particular pattern in the description.

This function downloads list of all datasets available on eurostat and return list of names of datasets that contains particular pattern in the dataset description.

E.g. all datasets related to education of teaching.

Usage

```
grepEurostatTOC(pattern)
```

Arguments

pattern Character, only datasets that contains this pattern in the description will be returned.

Value

A data.frame with eight columns

title	The name of dataset of theme
code	The codename of dataset of theme, will be used by the <code>getEurostatRCV</code> and <code>getEurostatRaw</code> functions.
type	Is it a dataset, folder or table.
last.update.of.data, last.table.structure.change, data.start, data.end	Dates.

Author(s)

Przemyslaw Biecek

See Also

See Also as [getEurostatRCV](#), [getEurostatRaw](#), [getEurostatTOC](#).

Examples

```
## Not run:
tmp <- grepEurostatTOC("education")
head(tmp)

## End(Not run)
```

maturaExam	<i>Results from Matura Exams in Poland for Math and Language for Years 2010-2015</i>
------------	--

Description

This dataset is created based on data from ZPD package, see <https://github.com/zozlak/ZPD> and <http://zpd.ibe.edu.pl/doku.php?id=obazie>. Each row shows results for one person that takes matura exams in a given year.

Author(s)

Przemyslaw Biecek [based on IBE / ZPD data]

Examples

```
## Not run:
data(maturaExam)
head(maturaExam)

## End(Not run)
```

Index

* database

- Bank Danych Lokalnych, [3](#)
- Dark Sky API for weather forecast, [5](#)
- getEurostatDictionary, [7](#)
- getEurostatRaw, [8](#)
- getEurostatRCV, [9](#)
- getEurostatTOC, [10](#)
- grepEurostatTOC, [12](#)

* datasets

- cities_lon_lat, [4](#)
- countries, [5](#)
- maturaExam, [13](#)

* geolocalisation

- getGoogleMapsAddress, [11](#)

* package

- SmarterPoland-package, [2](#)

Bank Danych Lokalnych, [3](#)

BDLtree (Bank Danych Lokalnych), [3](#)

cities_lon_lat, [4](#)

countries, [5](#)

Dark Sky API for weather forecast, [5](#)

getBDLsearch (Bank Danych Lokalnych), [3](#)

getBDLseries, [2](#)

getBDLseries (Bank Danych Lokalnych), [3](#)

getBDLtree (Bank Danych Lokalnych), [3](#)

getEurostatDictionary, [7](#)

getEurostatRaw, [7](#), [8](#), [8](#), [9](#), [10](#), [13](#)

getEurostatRCV, [2](#), [7](#), [9](#), [10](#), [13](#)

getEurostatTOC, [8](#), [9](#), [10](#), [13](#)

getGoogleMapsAddress, [11](#)

getMillwardBrown, [2](#), [12](#)

getMPgminy (Bank Danych Lokalnych), [3](#)

getMPpowiaty (Bank Danych Lokalnych), [3](#)

getMPwojewództwa (Bank Danych Lokalnych), [3](#)

getWeatherForecast, [2](#)

getWeatherForecast (Dark Sky API for weather forecast), [5](#)

grepEurostatTOC, [7–10](#), [12](#)

maturaExam, [13](#)

SmarterPoland (SmarterPoland-package), [2](#)

SmarterPoland-package, [2](#)