

Package ‘coloc’

June 14, 2021

Type Package

Imports data.table, ggplot2, methods, viridis, stats, grDevices,
susieR (>= 0.11.33), utils

Suggests knitr, testthat, snpStats, mvtnorm, magrittr, rmarkdown

Title Colocalisation Tests of Two Genetic Traits

Version 5.1.0

Date 2021-06-08

Maintainer Chris Wallace <cew54@cam.ac.uk>

Description Performs the colocalisation tests described in
Giambartolomei et al (2013) <[doi:10.1371/journal.pgen.1004383](https://doi.org/10.1371/journal.pgen.1004383)>,
Wallace (2020) <[doi:10.1371/journal.pgen.1008720](https://doi.org/10.1371/journal.pgen.1008720)>,
Wallace (2021) <[doi:10.1101/2021.02.23.432421](https://doi.org/10.1101/2021.02.23.432421)>.

License GPL

LazyLoad yes

VignetteBuilder knitr

RoxygenNote 7.1.1

Encoding UTF-8

URL <https://github.com/chr1swallace/coloc>

BugReports <https://github.com/chr1swallace/coloc/issues>

Collate 'check.R' 'claudia.R' 'coloc-package.R' 'plot.R' 'private.R'
'sensitivity.R' 'split.R' 'susie.R' 'testdata.R' 'zzz.R'

Depends R (>= 2.10)

NeedsCompilation no

Author Chris Wallace [aut, cre],
Claudia Giambartolomei [aut],
Vincent Plagnol [ctb]

Repository CRAN

Date/Publication 2021-06-14 15:10:01 UTC

R topics documented:

coloc-package	2
alpha_to_logbf	3
approx.bf.estimates	3
approx.bf.p	4
bin2lin	5
check_alignment	5
check_dataset	6
coloc.abf	8
coloc.bf_bf	9
coloc.detail	10
coloc.process	11
coloc.signals	12
coloc.susie	13
coloc.susie_bf	14
coloc_test_data	15
combine.abf	16
estgeno.l.ctl	16
est_cond	17
find.best.signal	18
finemap.abf	18
finemap.signals	19
logbf_to_pp	20
logdiff	21
logsum	21
map_cond	22
map_mask	23
plot.coloc_abf	23
plot_dataset	24
print.coloc_abf	25
process.dataset	25
runsusie	26
sdY.est	27
sensitivity	28
Var.data	29
Var.data.cc	30
Index	31

coloc-package

Colocalisation tests of two genetic traits

Description

Performs the colocalisation tests described in Plagnol et al (2009) and Wallace et al (2020) and draws some plots.

Author(s)

Chris Wallace cew54@cam.ac.uk

alpha_to_logbf *alpha_to_logbf*

Description

convert alpha matrix to log BF matrix

Usage

alpha_to_logbf(alpha, pi)

Arguments

alpha an L by p+1 matrix of posterior inclusion probabilities
pi per snp prior probability of causality

Value

L by p+1 matrix of log BF

Author(s)

Chris Wallace

approx.bf.estimates *Internal function, approx.bf.estimates*

Description

Internal function, approx.bf.estimates

Usage

approx.bf.estimates(z, V, type, suffix = NULL, sdY = 1)

Arguments

z normal deviate associated with regression coefficient and its variance
V its variance
type "quant" or "cc"
suffix suffix to append to column names of returned data.frame
sdY standard deviation of the trait. If not supplied, will be estimated.

Details

Calculate approximate Bayes Factors using supplied variance of the regression coefficients

Value

data.frame containing IABF and intermediate calculations

Author(s)

Vincent Plagnol, Chris Wallace

approx.bf.p	<i>Internal function, approx.bf.p</i>
-------------	---------------------------------------

Description

Internal function, approx.bf.p

Usage

```
approx.bf.p(p, f, type, N, s, suffix = NULL)
```

Arguments

p	p value
f	MAF
type	"quant" or "cc"
N	sample size
s	proportion of samples that are cases, ignored if type=="quant"
suffix	suffix to append to column names of returned data.frame

Details

Calculate approximate Bayes Factors

Value

data.frame containing IABF and intermediate calculations

Author(s)

Claudia Giambartolomei, Chris Wallace

bin2lin	<i>binomial to linear regression conversion</i>
---------	---

Description

Convert binomial to linear regression

Usage

```
bin2lin(D, dplot = FALSE)
```

Arguments

D	standard format coloc dataset
dplot	plot results if TRUE - useful for debugging

Details

Estimate beta and varbeta if a linear regression had been run on a binary outcome, given log OR and their variance + MAF in controls

sets $\beta = \text{cov}(x,y)/\text{var}(x)$ $\text{varbeta} = (\text{var}(y)/\text{var}(x) - \text{cov}(x,y)^2/\text{var}(x)^2)/N$

Value

D, with original beta and varbeta in beta.bin, varbeta.bin, and beta and varbeta updated to linear estimates

Author(s)

Chris Wallace

check_alignment	<i>check alignment</i>
-----------------	------------------------

Description

check alignment between beta and LD

Usage

```
check_alignment(D, thr = 0.2, do_plot = TRUE)
```

```
check.alignment(...)
```

Arguments

D	a coloc dataset
thr	plot SNP pairs in absolute LD > thr
do_plot	if TRUE (default) plot the diagnostic
...	arguments passed to check_alignment()

Value

proportion of pairs that are positive

Author(s)

Chris Wallace

check_dataset	<i>check_dataset</i>
---------------	----------------------

Description

Check coloc dataset inputs for errors

Usage

```
check_dataset(d, suffix = "", req = c("snp"), warn.minp = 1e-06)
check.dataset(...)
```

Arguments

d	dataset to check
suffix	string to identify which dataset (1 or 2)
req	names of elements that must be present
warn.minp	print warning if no p value < warn.minp
...	arguments passed to check_dataset()

Details

Coloc is flexible, requiring perhaps only p values, or z scores, or effect estimates and standard errors, but with this flexibility, also comes difficulties describing exactly the combinations of items required.

pvalues P-values for each SNP in dataset 1

N Number of samples in dataset 1

MAF minor allele frequency of the variants

beta regression coefficient for each SNP from dataset 1

varbeta variance of beta

type the type of data in dataset 1 - either "quant" or "cc" to denote quantitative or case-control

s for a case control dataset, the proportion of samples in dataset 1 that are cases

sdY for a quantitative trait, the population standard deviation of the trait. if not given, it can be estimated from the vectors of varbeta and MAF

snp a character vector of snp ids, optional. If present, it will be used to merge dataset1 and dataset2. Otherwise, the function assumes dataset1 and dataset2 contain results for the same SNPs in the same order.

Some of these items may be missing, but you must always give type.

Then scalars describing the samples used:

N

if type=="cc" s

if type=="quant" **and** sdY **known** sdY

If sdY is unknown, it will be approximated, and this will require

beta, varbeta, N, MAF

Then, if not already covered above, the summary statistics describing the results

preferably beta, varbeta

alternatively pvalues, MAF

check_dataset call stop() unless a series of expectations on dataset input format are met

This is a helper function for use by other coloc functions, but you can use it directly to check the format of a dataset to be supplied to coloc.abf(), coloc.signals(), finemap.abf(), or finemap.signals().

Value

NULL if no errors found

Author(s)

Chris Wallace

`coloc.abf`*Fully Bayesian colocalisation analysis using Bayes Factors*

Description

Bayesian colocalisation analysis

Usage

```
coloc.abf(dataset1, dataset2, MAF = NULL, p1 = 1e-04, p2 = 1e-04, p12 = 1e-05)
```

Arguments

<code>dataset1</code>	a list with specifically named elements defining the dataset to be analysed. See check_dataset for details.
<code>dataset2</code>	as above, for dataset 2
<code>MAF</code>	Common minor allele frequency vector to be used for both <code>dataset1</code> and <code>dataset2</code> , a shorthand for supplying the same vector as parts of both datasets
<code>p1</code>	prior probability a SNP is associated with trait 1, default 1e-4
<code>p2</code>	prior probability a SNP is associated with trait 2, default 1e-4
<code>p12</code>	prior probability a SNP is associated with both traits, default 1e-5

Details

This function calculates posterior probabilities of different causal variant configurations under the assumption of a single causal variant for each trait.

If regression coefficients and variances are available, it calculates Bayes factors for association at each SNP. If only p values are available, it uses an approximation that depends on the SNP's MAF and ignores any uncertainty in imputation. Regression coefficients should be used if available.

Value

a list of two `data.frames`:

- `summary` is a vector giving the number of SNPs analysed, and the posterior probabilities of H0 (no causal variant), H1 (causal variant for trait 1 only), H2 (causal variant for trait 2 only), H3 (two distinct causal variants) and H4 (one common causal variant)
- `results` is an annotated version of the input data containing log Approximate Bayes Factors and intermediate calculations, and the posterior probability `SNP.PP.H4` of the SNP being causal for the shared signal *if* H4 is true. This is only relevant if the posterior support for H4 in `summary` is convincing.

Author(s)

Claudia Giambartolomei, Chris Wallace

`coloc.bf_bf`*Coloc data through Bayes factors*

Description

Colocalise two datasets represented by Bayes factors

Usage

```
coloc.bf_bf(  
  bf1,  
  bf2,  
  p1 = 1e-04,  
  p2 = 1e-04,  
  p12 = 5e-06,  
  overlap.min = 0.5,  
  trim_by_posterior = TRUE  
)
```

Arguments

<code>bf1</code>	named vector of BF, or matrix of BF with colnames (cols=snp, rows=signals)
<code>bf2</code>	named vector of BF, or matrix of BF with colnames (cols=snp, rows=signals)
<code>p1</code>	prior probability a SNP is associated with trait 1, default 1e-4
<code>p2</code>	prior probability a SNP is associated with trait 2, default 1e-4
<code>p12</code>	prior probability a SNP is associated with both traits, default 1e-5
<code>overlap.min</code>	see <code>trim_by_posterior</code>
<code>trim_by_posterior</code>	

it is important that the signals to be colocalised are covered by adequate numbers of snps in both datasets. If TRUE, signals for which snps in common do not capture least `overlap.min` proportion of their posteriors support are dropped and colocalisation not attempted.

Details

This is the workhorse behind many coloc functions

Value

coloc.signals style result

Author(s)

Chris Wallace

`coloc.detail`*Bayesian colocalisation analysis with detailed output*

Description

Bayesian colocalisation analysis, detailed output

Usage

```
coloc.detail(  
  dataset1,  
  dataset2,  
  MAF = NULL,  
  p1 = 1e-04,  
  p2 = 1e-04,  
  p12 = 1e-05  
)
```

Arguments

<code>dataset1</code>	a list with specifically named elements defining the dataset to be analysed. See check_dataset for details.
<code>dataset2</code>	as above, for dataset 2
<code>MAF</code>	Common minor allele frequency vector to be used for both <code>dataset1</code> and <code>dataset2</code> , a shorthand for supplying the same vector as parts of both datasets
<code>p1</code>	prior probability a SNP is associated with trait 1, default 1e-4
<code>p2</code>	prior probability a SNP is associated with trait 2, default 1e-4
<code>p12</code>	prior probability a SNP is associated with both traits, default 1e-5

Details

This function replicates `coloc.abf`, but outputs more detail for further processing using `coloc.process`. Intended to be called internally by `coloc.signals`

Value

a list of three `data.table`s:

- `summary` is a vector giving the number of SNPs analysed, and the posterior probabilities of H0 (no causal variant), H1 (causal variant for trait 1 only), H2 (causal variant for trait 2 only), H3 (two distinct causal variants) and H4 (one common causal variant)
- `df` is an annotated version of the input data containing log Approximate Bayes Factors and intermediate calculations, and the posterior probability `SNP.PP.H4` of the SNP being causal for the shared signal
- `df3` is the same for all 2 SNP H3 models

Author(s)

Chris Wallace

See Also[coloc.process](#), [coloc.abf](#)

coloc.process

*Post process a coloc.details result using masking***Description**

Internal helper function

Usage

```

coloc.process(
  obj,
  hits1 = NULL,
  hits2 = NULL,
  LD = NULL,
  r2thr = 0.01,
  p1 = 1e-04,
  p2 = 1e-04,
  p12 = 1e-06,
  LD1 = LD,
  LD2 = LD,
  mode = c("iterative", "allbutone")
)

```

Arguments

obj	object returned by coloc.detail()
hits1	lead snps for trait 1. If length > 1, will use masking
hits2	lead snps for trait 2. If length > 1, will use masking
LD	named LD matrix (for masking)
r2thr	r2 threshold at which to mask
p1	prior probability a SNP is associated with trait 1, default 1e-4
p2	prior probability a SNP is associated with trait 2, default 1e-4
p12	prior probability a SNP is associated with both traits, default 1e-5
LD1	named LD matrix (for masking) for trait 1 only
LD2	named LD matrix (for masking) for trait 2 only
mode	either "iterative" (default) - successively condition on signals or "allbutone" - find all putative signals and condition on all but one of them in each analysis

Value

data.table of coloc results

Author(s)

Chris Wallace

coloc.signals

Coloc with multiple signals per trait

Description

New coloc function, builds on coloc.abf() by allowing for multiple independent causal variants per trait through conditioning or masking.

Usage

```
coloc.signals(  
  dataset1,  
  dataset2,  
  MAF = NULL,  
  LD = NULL,  
  method = c("single", "cond", "mask"),  
  mode = c("iterative", "allbutone"),  
  p1 = 1e-04,  
  p2 = 1e-04,  
  p12 = NULL,  
  maxhits = 3,  
  r2thr = 0.01,  
  pthr = 1e-06  
)
```

Arguments

dataset1	a list with specifically named elements defining the dataset to be analysed. See check_dataset for details.
dataset2	as above, for dataset 2
MAF	Common minor allele frequency vector to be used for both dataset1 and dataset2, a shorthand for supplying the same vector as parts of both datasets
LD	required if method="cond". matrix of genotype <i>correlation</i> (ie r, not r ²) between SNPs. If dataset1 and dataset2 may have different LD, you can instead add LD=LD1 to the list of dataset1 and a different LD matrix for dataset2
method	default "" means do no conditioning, should return similar to coloc.abf. if method="cond", then use conditioning to coloc multiple signals. if method="mask", use masking to coloc multiple signals. if different datasets need different methods (eg LD is only available for one of them) you can set method on a per-dataset basis by adding method="..." to the list for that dataset.

mode	<p>"iterative" or "allbutone". Easiest understood with an example. Suppose there are 3 signal SNPs detected for trait 1, A, B, C and only one for trait 2, D.</p> <p>Under "iterative" mode, 3 coloc will be performed:</p> <ul style="list-style-type: none"> * trait 1 - trait 2 * trait 1 conditioned on A - trait 2 * trait 1 conditioned on A+B - trait 2 <p>Under "allbutone" mode, they would be</p> <ul style="list-style-type: none"> * trait 1 conditioned on B+C - trait 2 * trait 1 conditioned on A+C - trait 2 * trait 1 conditioned on A+B - trait 2 <p>Only iterative mode is supported for method="mask".</p> <p>The allbutone mode is optimal if the signals are known with certainty (which they never are), because it allows each signal to be tested without influence of the others. When there is uncertainty, it may make sense to use iterative mode, because the strongest signals aren't affected by conditioning incorrectly on weaker secondary and less certain signals.</p>
p1	prior probability a SNP is associated with trait 1, default 1e-4
p2	prior probability a SNP is associated with trait 2, default 1e-4
p12	prior probability a SNP is associated with both traits, default 1e-5
maxhits	maximum number of levels to condition/mask
r2thr	if masking, the threshold on r2 should be used to call two signals independent. our experience is that this needs to be set low to avoid double calling the same strong signal.
pthr	if masking or conditioning, what p value threshold to call a secondary hit "significant"

Value

data.table of coloc results, one row per pair of lead snps detected in each dataset

Author(s)

Chris Wallace

coloc.susie

run coloc using susie to detect separate signals

Description

colocalisation with multiple causal variants via SuSiE

Usage

```

coloc.susie(
  dataset1,
  dataset2,
  back_calculate_lbf = FALSE,
  susie.args = list(),
  ...
)

```

Arguments

dataset1	<i>either</i> a coloc-style input dataset (see check_dataset), or the result of running runsusie on such a dataset
dataset2	<i>either</i> a coloc-style input dataset (see check_dataset), or the result of running runsusie on such a dataset
back_calculate_lbf	by default, use the log Bayes factors returned by <code>susie_rss</code> . It is also possible to back-calculate these from the posterior probabilities. It is not advised to set this to TRUE, the option exists really for testing purposes only.
susie.args	a named list of additional arguments to be passed to runsusie
...	other arguments passed to coloc.bf_bf , in particular prior values for causal association with one trait (p1, p2) or both (p12)

Value

a list, containing elements * summary a data.table of posterior probabilities of each global hypothesis, one row per pairwise comparison of signals from the two traits * results a data.table of detailed results giving the posterior probability for each snp to be jointly causal for both traits *assuming H4 is true*. Please ignore this column if the corresponding posterior support for H4 is not high. * priors a vector of the priors used for the analysis

Author(s)

Chris Wallace

coloc.susie_bf	<i>run coloc using susie to detect separate signals</i>
----------------	---

Description

coloc for susie output + a separate BF matrix

Usage

```
coloc.susie_bf(dataset1, bf2, p1 = 1e-04, p2 = 1e-04, p12 = 5e-06, ...)
```

Arguments

dataset1	a list with specifically named elements defining the dataset to be analysed. See check_dataset for details.
bf2	named vector of BF, names are snp ids and will be matched to column names of susie object's alpha
p1	prior probability a SNP is associated with trait 1, default 1e-4
p2	prior probability a SNP is associated with trait 2, default 1e-4
p12	prior probability a SNP is associated with both traits, default 1e-5
...	other arguments passed to coloc.bf_bf , in particular prior values for causal association with one trait (p1, p2) or both (p12)

Value

coloc.signals style result

Author(s)

Chris Wallace

coloc_test_data *Simulated data to use in testing and vignettes in the coloc package*

Description

Simulated data to use in testing and vignettes in the coloc package

Usage

```
data(coloc_test_data)
```

Format

A four of two coloc-style datasets. Elements D1 and D2 have a single shared causal variant, and 50 SNPs. Elements D3 and D4 have 100 SNPs, one shared causal variant, and one variant unique to D3. Use these as examples of what a coloc-style dataset for a quantitative trait should look like.

Examples

```
data(coloc_test_data)
names(coloc_test_data)
str(coloc_test_data$D1)
check_dataset(coloc_test_data$D1) # should return NULL if data structure is ok
```

combine.abf	<i>combine.abf</i>
-------------	--------------------

Description

Internal function, calculate posterior probabilities for configurations, given logABFs for each SNP and prior probs

Usage

```
combine.abf(l1, l2, p1, p2, p12)
```

Arguments

l1	merged.df\$IABF.df1
l2	merged.df\$IABF.df2
p1	prior probability a SNP is associated with trait 1, default 1e-4
p2	prior probability a SNP is associated with trait 2, default 1e-4
p12	prior probability a SNP is associated with both traits, default 1e-5

Value

named numeric vector of posterior probabilities

Author(s)

Claudia Giambartolomei, Chris Wallace

estgeno.1.ctf	<i>estgeno1</i>
---------------	-----------------

Description

Estimate single snp frequency distributions

Usage

```
estgeno.1.ctf(f)
```

```
estgeno.1.cse(G0, b)
```

Arguments

f	MAF
G0	single snp frequency in controls (vector of length 3) - obtained from estgeno.1.ctf
b	log odds ratio

Value

relative frequency of genotypes 0, 1, 2

Author(s)

Chris Wallace

See Also

estgeno2

est_cond

generate conditional summary stats

Description

Internal helper function for est_all_cond

Usage

```
est_cond(x, LD, YY, sigsnps, xtx = NULL)
```

Arguments

x	coloc dataset
LD	named matrix of r
YY	sum((Y-Ybar)^2)
sigsnps	names of snps to jointly condition on
xtx	optional, matrix X'X where X is the genotype matrix. If not available, will be estimated from LD, MAF, beta and sample size (the last three should be part of the coloc dataset)

Value

data.table giving snp, beta and varbeta on remaining snps after conditioning

Author(s)

Chris Wallace

find.best.signal *Pick out snp with most extreme Z score*

Description

Internal helper function

Usage

```
find.best.signal(D)
```

Arguments

D standard format coloc dataset

Value

z at most significant snp, named by that snp id

Author(s)

Chris Wallace

finemap.abf *Bayesian finemapping analysis*

Description

Bayesian finemapping analysis

Usage

```
finemap.abf(dataset, p1 = 1e-04)
```

Arguments

dataset a list with specifically named elements defining the dataset to be analysed. See [check_dataset](#) for details.

p1 prior probability a SNP is associated with the trait 1, default 1e-4

Details

This function calculates posterior probabilities of different causal variant for a single trait.

If regression coefficients and variances are available, it calculates Bayes factors for association at each SNP. If only p values are available, it uses an approximation that depends on the SNP's MAF and ignores any uncertainty in imputation. Regression coefficients should be used if available.

Value

a data.frame:

- an annotated version of the input data containing log Approximate Bayes Factors and intermediate calculations, and the posterior probability of the SNP being causal

Author(s)

Chris Wallace

 finemap.signals

Finemap multiple signals in a single dataset

Description

This is an analogue to finemap.abf, adapted to find multiple signals where they exist, via conditioning or masking - ie a stepwise procedure

Usage

```
finemap.signals(
  D,
  LD = D$LD,
  method = c("single", "mask", "cond"),
  r2thr = 0.01,
  sigsnps = NULL,
  pthr = 1e-06,
  maxhits = 3
)
```

Arguments

D	list of summary stats for a single disease, see check_dataset
LD	matrix of signed r values (not rsq!) giving correlation between SNPs
method	if method="cond", then use conditioning to coloc multiple signals. The default is mask - this is less powerful, but safer because it does not assume that the LD matrix is properly allelically aligned to estimated effect
r2thr	if mask==TRUE, all snps will be masked with $r^2 > r2thr$ with any sigsnps. Otherwise ignored
sigsnps	SNPs already deemed significant, to condition on or mask, expressed as a numeric vector, whose <i>names</i> are the snp names
pthr	when $p > pthr$, stop successive searching
maxhits	maximum depth of conditioning. procedure will stop if $p > pthr$ OR $abs(z) < zthr$ OR maxhits hits have been found.
mask	use masking if TRUE, otherwise conditioning. defaults to TRUE

Value

list of successively significant fine mapped SNPs, named by the SNPs

Author(s)

Chris Wallace

logbf_to_pp	<i>logbf 2 pp</i>
-------------	-------------------

Description

convert logbf matrix to PP matrix

Usage

```
logbf_to_pp(bf, pi, last_is_null)
```

Arguments

bf	an L by p or p+1 matrix of log Bayes factors
pi	<i>either</i> a scalar representing the prior probability for any snp to be causal, <i>or</i> a full vector of per snp / null prior probabilities
last_is_null	TRUE if last value of the bf vector or last column of a bf matrix relates to the null hypothesis of no association. This is standard for SuSiE results, but may not be for BF constructed in other ways.

Value

matrix of posterior probabilities, same dimensions as bf

Author(s)

Chris Wallace

logdiff	<i>logdiff</i>
---------	----------------

Description

Internal function, logdiff

Usage

logdiff(x, y)

Arguments

x	numeric
y	numeric

Details

This function calculates the log of the difference of the exponentiated logs taking out the max, i.e. insuring that the difference is not negative

Value

$\max(x) + \log(\exp(x - \max(x,y)) - \exp(y - \max(x,y)))$

Author(s)

Chris Wallace

logsum	<i>logsum</i>
--------	---------------

Description

Internal function, logsum

Usage

logsum(x)

Arguments

x	numeric vector
---	----------------

Details

This function calculates the log of the sum of the exponentiated logs taking out the max, i.e. insuring that the sum is not Inf

Value
$$\max(x) + \log(\text{sum}(\exp(x - \max(x))))$$
Author(s)

Claudia Giambartolomei

map_cond

find the next most significant SNP, conditioning on a list of sigsnps

Description

Internal helper function for finemap.signals

Usage

```
map_cond(D, LD, YY, sigsnps = NULL)
```

Arguments

D	dataset in standard coloc format
LD	named matrix of r
YY	sum(y^2)
sigsnps	names of snps to mask

Value

named numeric - Z score named by snp

Author(s)

Chris Wallace

map_mask	<i>find the next most significant SNP, masking a list of sigsnps</i>
----------	--

Description

Internal helper function for finemap.signals

Usage

```
map_mask(D, LD, r2thr = 0.01, sigsnps = NULL)
```

Arguments

D	dataset in standard coloc format
LD	named matrix of r
r2thr	mask all snps with r2 > r2thr with any in sigsnps
sigsnps	names of snps to mask

Value

named numeric - Z score named by snp

Author(s)

Chris Wallace

plot.coloc_abf	<i>plot a coloc_abf object</i>
----------------	--------------------------------

Description

plot a coloc_abf object

Usage

```
## S3 method for class 'coloc_abf'  
plot(x, ...)
```

Arguments

x	coloc_abf object to be plotted
...	other arguments

Value

ggplot object

Author(s)

Chris Wallace

plot_dataset	<i>plot a coloc dataset</i>
--------------	-----------------------------

Description

Plot a coloc structured dataset

Usage

```
plot_dataset(
  d,
  susie_obj = NULL,
  alty = NULL,
  ylab = "-log10(p)",
  show_legend = TRUE,
  color = c("dodgerblue2", "green4", "#6A3D9A", "#FF7F00", "gold1", "skyblue2",
    "#FB9A99", "palegreen2", "#CAB2D6", "#FDBF6F", "gray70", "khaki2", "maroon",
    "orchid1", "deeppink1", "blue1", "steelblue4", "darkturquoise", "green1", "yellow4",
    "yellow3", "darkorange4", "brown"),
  ...
)
```

Arguments

d	a coloc dataset
susie_obj	optional, the output of a call to runsusie()
alty	default is to plot a standard manhattan. If you wish to plot a different y value, pass it here. You may also want to change ylab to describe what you are plotting.
ylab	label for y axis, default is -log10(p) and assumes you are plotting a manhattan
show_legend	optional, show the legend or not. default is TRUE
color	optional, specify the colours to use for each credible set when susie_obj is supplied. Default is shamelessly copied from susieR::susie_plot() so that colours will match
...	other arguments passed to the base graphics plot() function

Author(s)

Chris Wallace

print.coloc_abf *print.coloc_abf*

Description

Print summary of a coloc.abf run

Usage

```
## S3 method for class 'coloc_abf'  
print(x, ...)
```

Arguments

x object of class coloc_abf returned by coloc.abf() or coloc.signals()
... optional arguments: "trait1" name of trait 1, "trait2" name of trait 2

Value

x, invisibly

Author(s)

Chris Wallace

process.dataset *process.dataset*

Description

Internal function, process each dataset list for coloc.abf

Usage

```
process.dataset(d, suffix)
```

Arguments

d list
suffix "df1" or "df2"

Value

data.frame with log(abf) or log(bf)

Author(s)

Chris Wallace

 runsusie

Run susie on a single coloc-structured dataset

Description

run susie_rss storing some additional information for coloc

Usage

```

runsusie(
  d,
  suffix = 1,
  p = NULL,
  trimz = NULL,
  r2.prune = NULL,
  maxit = 100,
  repeat_until_convergence = TRUE,
  s_init = NULL,
  ...
)

```

Arguments

d	coloc dataset, must include LD (signed correlation matrix)
suffix	suffix label that will be printed with any error messages
p	prior probability a snp is causal (equivalent to p1 or p2 in coloc.abf). By default, this is set to NULL, upon which we will set a small null_weight to pass to susie_rss() (see vignette a06 for details why). You can override this by setting p as you would p1 or p2 in a coloc function, but note that you may miss some true signals that way. Also note that neither of these options correspond to the susie_rss() defaults, because our goal here is not fine mapping alone.
trimz	used to trim datasets for development purposes
r2.prune	sometimes SuSiE can return multiple signals in high LD. if you set r2.prune to a value between 0 and 1, sets with index SNPs with LD greater than r2.prune
maxit	maximum number of iterations for the first run of susie_rss(). If susie_rss() does not report convergence, runs will be extended assuming repeat_until_convergence=TRUE. Most users will not need to change this default.
repeat_until_convergence	keep running until susie_rss() indicates convergence. Default TRUE. If FALSE, susie_rss() will run with maxit iterations, and if not converged, runsusie() will error. Most users will not need to change this default.
s_init	used internally to extend runs that haven't converged. don't use.
...	arguments passed to susie_rss. In particular, if you want to match some coloc defaults, set

- prior_variance=0.2^2 (if a case-control trait) or (0.15/sd(Y))^2 if a quantitative trait
 - estimate_prior_variance=FALSE
- otherwise susie_rss will estimate the prior variance itself

Value

results of a susie_rss run, with some added dimnames

Author(s)

Chris Wallace

Examples

```
library(coloc)
data(coloc_test_data)
result=runsusie(coloc_test_data$D1)
summary(result)
```

sdY.est

Estimate trait variance, internal function

Description

Estimate trait standard deviation given vectors of variance of coefficients, MAF and sample size

Usage

```
sdY.est(vbeta, maf, n)
```

Arguments

vbeta	vector of variance of coefficients
maf	vector of MAF (same length as vbeta)
n	sample size

Details

Estimate is based on $\text{var}(\hat{\beta}) = \text{var}(Y) / (n * \text{var}(X))$ $\text{var}(X) = 2maf(1-maf)$ so we can estimate $\text{var}(Y)$ by regressing $n*\text{var}(X)$ against $1/\text{var}(\hat{\beta})$

Value

estimated standard deviation of Y

Author(s)

Chris Wallace

sensitivity *Prior sensitivity for coloc*

Description

Shows how prior and posterior per-hypothesis probabilities change as a function of p12

Usage

```
sensitivity(
  obj,
  rule = "",
  dataset1 = NULL,
  dataset2 = NULL,
  npoints = 100,
  doplot = TRUE,
  plot.manhattans = TRUE,
  preserve.par = FALSE,
  row = 1
)
```

Arguments

obj	output of coloc.detail or coloc.process
rule	a decision rule. This states what values of posterior probabilities "pass" some threshold. This is a string which will be parsed and evaluated, better explained by examples. "H4 > 0.5" says post prob of H4 > 0.5 is a pass. "H4 > 0.9 & H4/H3 > 3" says post prob of H4 must be > 0.9 AND it must be at least 3 times the post prob of H3."
dataset1	optional the dataset1 used to run SuSiE. This will be used to make a Manhattan plot if plot.manhattans=TRUE.
dataset2	optional the dataset2 used to run SuSiE. This will be used to make a Manhattan plot if plot.manhattans=TRUE.
npoints	the number of points over which to evaluate the prior values for p12, equally spaced on a log scale between p1*p2 and min(p1,p2) - these are logical limits on p12, but not scientifically sensible values.
doplot	draw the plot. set to FALSE if you want to just evaluate the prior and posterior matrices and work with them yourself
plot.manhattans	if TRUE, show Manhattans of input data
preserve.par	if TRUE, do not change par() of current graphics device - this is to allow sensitivity plots to be incorporated into a larger set of plots, or to be plot one per page on a pdf, forexample
row	when coloc.signals() has been used and multiple rows are returned in the coloc summary, which row to plot

Details

Function is called mainly for plotting side effect. It draws two plots, showing how prior and posterior probabilities of each coloc hypothesis change with changing p12. A decision rule sets the values of the posterior probabilities considered acceptable, and is used to shade in green the region of the plot for which the p12 prior would give an acceptable result. The user is encouraged to consider carefully whether some prior values shown within the green shaded region are sensible before accepting the hypothesis. If no shading is shown, then no priors give rise to an accepted result.

Value

list of 3: prior matrix, posterior matrix, and a pass/fail indicator (returned invisibly)

Author(s)

Chris Wallace

Var.data

Var.data

Description

variance of MLE of beta for quantitative trait, assuming $\text{var}(y)=1$

Usage

```
Var.data(f, N)
```

Arguments

f	minor allele freq
N	sample number

Details

Internal function

Value

variance of MLE beta

Author(s)

Claudia Giambartolomei

Var.data.cc

Var.data

Description

variance of MLE of beta for case-control

Usage

Var.data.cc(f, N, s)

Arguments

f	minor allele freq
N	sample number
s	???

Details

Internal function

Value

variance of MLE beta

Author(s)

Claudia Giambartolomei

Index

- * **datasets**
 - coloc_test_data, 15
- * **package**
 - coloc-package, 2
- alpha_to_logbf, 3
- approx.bf.estimates, 3
- approx.bf.p, 4
- bin2lin, 5
- check.alignment (check_alignment), 5
- check.dataset (check_dataset), 6
- check_alignment, 5
- check_dataset, 6, 8, 10, 12, 14, 15, 18, 19
- coloc-package, 2
- coloc.abf, 8, 11
- coloc.bf_bf, 9, 14, 15
- coloc.detail, 10
- coloc.process, 11, 11
- coloc.signals, 12
- coloc.susie, 13
- coloc.susie_bf, 14
- coloc_test_data, 15
- combine.abf, 16
- est_cond, 17
- estgeno.1.cse (estgeno.1.ctl), 16
- estgeno.1.ctl, 16
- find.best.signal, 18
- finemap.abf, 18
- finemap.signals, 19
- logbf_to_pp, 20
- logdiff, 21
- logsum, 21
- map_cond, 22
- map_mask, 23
- plot.coloc_abf, 23
- plot_dataset, 24
- print.coloc_abf, 25
- process.dataset, 25
- runsusie, 14, 26
- sdY.est, 27
- sensitivity, 28
- Var.data, 29
- Var.data.cc, 30